


Note1: U-WAVE fit and Bluetooth®U-WAVE fit can only be connected to digimatic calipers, digimatic micrometers, and some digimatic indicators with a measurement range of 0 to 300 mm.

Refer to the lists of compatible models on pages 32 to 35 for details.

Note2: U-WAVE should only be used in countries where they have obtained wireless certification.

Product combinations

Digimatic gage	Connecting unit/connecting cable	Transmitter	Receiver
Digimatic micrometers	02AZF310	Buzzer type U-WAVE-TM 264-623	 <p>U-WAVE-R 02AZD810D</p> <p>Design registered in Japan</p>
		or	
Digimatic caliper	Standard type 02AZF300	Buzzer type U-WAVE-TC 264-621	
	Coolant-proof type 02AZF310	IP67 type U-WAVE-TC 264-620	
Digimatic indicator, Other	ID-CNX/ID-FNX series (12.7mm type only) 02AZF700	Buzzer type U-WAVE-TM 264-623	
	Other Connecting cable Bracket	IP67 type U-WAVE-TM 264-622	
		Buzzer type U-WAVE-T 02AZD880G	
		IP67 type U-WAVE-T 02AZD730G	

Product combinations **No receiver necessary**

Digimatic gage	Connecting unit/connecting cable	Transmitter
Digimatic micrometers	02AZF310	Buzzer type U-WAVE-TMB 264-627
		or
Digimatic caliper	Standard type 02AZF300	Buzzer type U-WAVE-TCB 264-625
	Coolant-proof type 02AZF310	IP67 type U-WAVE-TCB 264-624
Digimatic indicator	ID-CNX/ID-FNX series (12.7 mm type only) 02AZF700	Buzzer type U-WAVE-TMB 264-627
		IP67 type U-WAVE-TMB 264-626